


A400P Datasheet

Modular Analog Telephony Interface Product

Document Rev 0.02., written by: James.zhu@openvox.cn

A400P/A400E is a 4-port analog card and works with PSTN line. It can be used to build a PBX system based on Asterisk Open Source platform.

Key Benefits:

- Modular Design: Up to 4 FXS, FXO or mixed FXS/FXO ports per card
- Scalable: Just add additional cards to extend system
- Easy to use: Full software and hardware compatible with Digium™'s TDM400P. You can use Digium's X100M/S100M module on this card, or use OpenVox FXO-100/ FXS-100 Module on TDM400P.
- World Wide Usable: Configurable line interface to meet global telephone line interface requirements
- High quality with low price
- Application ready: Use Asterisk® to build your IP-PBX/Voicemail system

Features:

- Support Industry Standard: PCI 2.2 and PCI Express (for A400E)
- Both 3.3 V and 5 V PCI slot can be used for A400P
- Support GPL Software driver used with zaptel

Hardware and Software Requirements:

- RAM 128 + MB
- Linux kernel 2.4.X or 2.6.X
- CPU 800+ MHZ
- PCI 2.2 or PCI Express

Physical Information:

| Name | Net weight (g) | Size (cm) |
|-------|----------------|---------------|
| A400P | 82 | 13.8*10.2*1.8 |
| A400E | 89 | 13.8*11.1*1.8 |

Misc:

- Temperature Operation: 0 to 50°C
- Temperature Storage: - 40 to 125°C
- Humidity: 10 TO 90% NON-CONDENSING
- Voltage: 5/12V, 3REN
- Power Dissipation Max: 2.77W/11.6W

Digium™ is a trademark of Digium, Inc

Asterisk® is a registered trademark of Digium, Inc