

fit-PC3 Specifications

17-Jan-2012

System

Feature	fit-PC3 Model				Notes
	Value	Basic	LP	Pro	
CPU	AMD G-T44R 64 bit single core 1 GHz 9W TDP	AMD G-T40N 64 bit dual core 1 GHz 9W TDP	AMD G-T40E 64 bit dual core 1 GHz 6.4W TDP	AMD G-T56N 64 bit dual core 1.65 GHz 18W TDP	
RAM	Up to 8 GB, DDR3-1066, 64-bit (two SO-DIMM sockets)				Configurable
Storage	Internal 2.5" hard disk Two eSATA ports, up to 6 Gbit/s				Configurable

Graphics

Feature	fit-PC3 Model				Notes
	Value	Basic	LP	Pro	
GPU	Radeon HD 6250	Radeon HD 6290	Radeon HD 6250	Radeon HD 6320	
HDMI	HDMI 1.3a Up to 1920 x 1200 @ 60 Hz			HDMI 1.4a Up to 1920 x 1200 @ 60 Hz	
DisplayPort	Up to 1920 x 1200 at 60Hz			Up to 2560 x 1600 at 60Hz	

I/O

Feature	fit-PC3 Model				Notes
	Value	Basic	LP	Pro	
Audio	Stereo line-out and stereo line-in 7.1 channel S/PDIF, (electrical through 3.5mm jack)				
Network	1000 BaseT Ethernet port, activity LEDs, RJ-45 connector 802.11b/g/n Wi-Fi, 2 antennas, 150 Mbit/s BT 3.0				Optional half-size Mini PCIe module
USB	Two USB 3.0 host ports, 5 Gbit/s Two USB 2.0 host ports, 480 Mbit/s Four USB 2.0 host ports, 480 Mbit/s in front				Optional FACE Module
RS232	Partial modem controls, ultra mini serial connector				
Expansion	Mini PCIe socket, half-size Mini PCIe socket, full-size Proprietary FACE Module (Function And Connectivity Extension Module): 4x PCIe lanes 6x USB2 2x SATA 30x GPIOs 2x SMBus LPC				Used for wireless module

Electrical and Mechanical

Feature	fit-PC3 Model				Notes
	Value	Basic	LP	Pro	
Power supply	Unregulated 10 to 16 volt input				
Power	8W – 17W	8W – 17W	7W – 15W	9W – 24W	Depends on system load
Dimensions	16cm x 16cm x 2.5cm			19cm x 16cm x 4cm	